2621 Ridgepoint Drive, Suite 235 Austin, TX 78754 800.866.6506 (US) www.ikey.com

SLK-102-TP-FL

Cleanable Sealed Medical Keyboard with Touchpad

Designed for the infection control challenges of todayâ€™s healthcare environment, the SlimKey-MD™ SLK-102-TP-FL medical keyboard is ideal for use in an array of c linical settings. It is manufactured with an integrated GlidePoint™ touchpad pointing d evice and red LED backlit keys. Featuring a sealed industrial silicone keypad and low-profile keys, the SlimKey-MD™ SLK-102-TP-FL is easily disinfected using any h ospital cleaning agent. Other standard features include 12 function keys and an oversized numeric pad. SlimKey-MD™ medical keyboards are compatible with g ermicidal sprays and wipes, making them ideal for use in ORs, patient rooms, on carts and at nursing stations.

Technical Specifications

Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10' straight (3 m)
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.040 in. (1mm) ACTUATION FORCE: 4.76 oz. +/- 1.06 oz. (135g +/- 30g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	USB: 210mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB
Compatability	USB KEYBOARD/TOUCHPAD: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +65C (-40F to +149F) OPERATING: 0C to +60C (+32F to +140F)
Weight	1.75 lbs +/- 0.10 lbs (0.79 kg +/- 0.05 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	14.85" x 5.87" x 0.86" (w-h-d) 377.2mm x 149.1mm x 21.9mm

Features and Benefits

- Cleanable, Liquidproof Design
- Integrated Backlighting
- USB configurations available
- Integrated 10-Key Numeric Pad
- Low-profile keys for easy cleaning

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)